



# MONITOR SE



## Discover superior audio performance, without the cost.

The stylish and affordable new Monitor SE Series is the perfect introduction to the world of high performance audio. Sure it's packed with state-of-the-art technology, the kind of stuff only found on speakers that cost much more. But more important, the new Monitor SE Series is part of the Paradigm family of high performance loudspeakers, and just like all Paradigm loudspeakers it's engineered to change the way you think and feel about your entertainment.

## ADVANCED TECHNOLOGY INCLUDES:

- Poly Cones with inverted caps, reverse roll surrounds and S-PAL™ Tweeters.
- Perforated Phase Alignment (PPA™) Tweeter Lens smooths extended high frequency response for incredible detail.
- Computer optimized second-order crossovers, engineered for seamless dynamic integration



Matte Black



Gloss White



	<b>MONITOR SE 6000F</b>	<b>MONITOR SE 3000F</b>	<b>MONITOR SE 2000C</b>	<b>MONITOR SE ATOM</b>
<b>Design</b>	5-driver, 3-way bass reflex floorstanding	4-driver, 3-way bass reflex floorstanding	3-driver, 2-way bass reflex center channel	2-driver, 2-way bass reflex bookshelf
<b>Crossover</b>	2nd-order electroacoustic at 3.0 kHz (tweeter/mid) and 800Hz (mid/woofers)	2nd-order electroacoustic at 3.0kHz (tweeter/mid) and 800Hz (mid/woofers)	2nd-order electroacoustic at 2.0kHz	2nd-order electroacoustic at 2.3kHz
<b>High Frequency Driver</b>	1" (25mm) S-PAL™ dome, ferro-fluid damped / cooled, Perforated Phase-Aligning (PPA™) Tweeter Lens	1" (25mm) S-PAL™ dome, ferro-fluid damped / cooled, Perforated Phase-Aligning (PPA™) Tweeter Lens	1" (25mm) S-PAL™ dome, ferro-fluid damped / cooled, Perforated Phase-Aligning (PPA™) Tweeter Lens	1" (25mm) S-PAL™ dome, ferro-fluid damped / cooled, Perforated Phase-Aligning (PPA™) Tweeter Lens
<b>Midrange Driver</b>	5-1/2" (140mm) mineral filled polypropylene cone/inverted dust cap/downroll surround	5-1/2" (140mm) mineral filled polypropylene cone/inverted dust cap/downroll surround	N/A	N/A
<b>Bass/Midrange Driver</b>	N/A	N/A	Two 5-1/2" (140mm) mineral filled polypropylene cones	5-1/2" (140mm) mineral filled polypropylene cone
<b>Bass Driver</b>	Three 5-1/2" (140mm) mineral-filled polypropylene cones / inverted dust cap / downroll surrounds	Two 5-1/2" (140mm) mineral-filled polypropylene cones / inverted dust cap / downroll surrounds	N/A	N/A
<b>Low Frequency Extension</b>	43Hz	44Hz	53Hz	45Hz
<b>Frequency Response (On Axis)</b>	+/- 3dB from 53Hz - 21kHz	+/- 3dB from 55Hz - 21kHz	+/- 3dB from 65Hz - 21kHz	+/- 3dB from 61Hz - 21kHz
<b>Frequency Response (30°)</b>	+/- 3dB from 53Hz - 17kHz	+/- 3dB from 55Hz - 17kHz	+/- 3dB from 65Hz - 17kHz	+/- 3dB from 61Hz - 17kHz
<b>Sensitivity - Room</b>	93 dB	91 dB	93 dB	89 dB
<b>Sensitivity - Anechoic</b>	90 dB	88 dB	90 dB	86 dB
<b>Suitable Amplifier Power Range</b>	15-130W	15-130W	15-100W	15-100W
<b>Maximum Input Power</b>	100 Watts	100 Watts	50 Watts	50 Watts
<b>Impedance</b>	Compatible with 8 ohms	Compatible with 8 ohms	Compatible with 8 ohms	Compatible with 8 ohms
<b>Overall Dimensions (h x w x d)</b>	41-1/4" x 9" x 14-1/8" (105 cm x 23 cm x 36 cm)	39-1/2" x 9" x 11-1/8" (100.4 cm x 23 cm x 28cm)	7-1/4" x 19-3/4" x 11-1/8" (18.3 cm x 50 cm x 28 cm)	12-3/4" x 7-1/8" x 11" (32 cm x 18 cm x 27 cm)
<b>Weight</b>	44lb (19.9kg) each	35lb (15.8kg) each	19lb (8.6kg) each	12lb (5.4kg) each
<b>Finish</b>	Matte Black, Gloss White	Matte Black, Gloss White	Matte Black, Gloss White	Matte Black, Gloss White

Specifications are subject to change without notice.  
Stands Are Sold Separately.

Dimensions include grille and terminal posts for all models. Includes feet for Monitor SE 6000F and Monitor SE 3000F. Includes isolation pads for center channel and bookshelf speakers.